



DASH

— SERIES —



DASH

AVAILABLE DECK SIZES

34" & 42"



DASH XD

AVAILABLE DECK SIZES

34" - 48"

DASH XD

IDEAL FOR UP TO

3/4
ACRE

Heavy Duty Steel Frame

1" x 2" steel frame making it one of the toughest and most durable in its class

Welded Fabricated Steel Deck

Durable 11 ga. welded fabricated steel deck adds durability & extends mower's life. (compare to other brand's cheap stamped decks).

Foot Operated Deck Lift

Easily adjust the deck height between 1.5" - 4.5" with less effort than hand-operated levers found on other brands.

Premium Seat

Bolstered with built-in lumbar support.

18" BigBite™ Rear Tires

Up to 6 mph

Compact Size

Easily fits through most gates making backyard mowing easy and ideal for garage storage

Premium Power

V-Twin Kawasaki® engine

LIMITED
WARRANTY

2 YEAR | **200** HOUR

RESIDENTIAL



Standard Engine Guard





FEATURES FOUND ON THE DASH

DASH

IDEAL FOR UP TO

3/4
ACRE

- ✓ **16" Rear Tires**
- ✓ **Briggs and Stratton Engine**
Powerbuilt™ 10.5 HP
- ✓ **Compact Size**
Easily fits through most gates making backyard mowing easy and ideal for garage storage.



ACCESSORIES

- ▶ Mulch kit
- ▶ Grass bagger
(non-powered 2.0 bushels)
- ▶ Steering lever extension kit
- ▶ Light kit
- ▶ Engine Guard (Dash only)
- ▶ Armrest kit (Dash XD only)
- ▶ Stripe kit

LIMITED
WARRANTY

2 YEAR | **200** HOUR

RESIDENTIAL

DASH		DASH XD
ENGINE		
Manufacturer	Briggs and Stratton PowerBuilt™	Kawasaki® FR series
HP	10.5HP (Per SAE J1995)	34" & 42" deck: 15HP - FR541 48" deck: 18HP - FR600 (Per SAE J1995)
Displacement	344cc	603cc
DRIVE SYSTEM		
Type	Dual hydrostatic	
Transmission	Hydro-Gear® ZT1800®	
Speed	Up to 5 mph	Up to 6 mph
Parking Brakes	Patented automatic	
DECKS		
Cutting Width	Side discharge: 34", 42"	Side discharge: 34", 42", 48"
Cutting Heights	1.5" - 4.5"	
Deck Lift	Foot operated	
Depth	4.1"	
Blades	2	34" & 42": 2 48": 3
Blade Length	34" deck: 16.75" 42" deck: 20.50"	34": 16.75" 42": 20.50" 48": 16.5"
Blade Tip Speed	34": 17,500 42": 16,700	34": 17,500 42": 16,700 48": 17,200
Spindles	Aluminum with 3/4" shafts and triple protection sealed ball bearings	
Drive	Electric PTO clutch	
Construction	Fabricated 11 ga. steel	
Spindle Mounts	Reinforced 14 ga. steel	
Impact/Trim Areas	1/4" x 3/4" steel bar	
CONSTRUCTION		
Frame	1" x 2" steel tubing	
Front Axle	Fabricated with sealed ball bearings	
Front Caster Wheels	Commercial duty steel roller bearings	
Front Caster Forks	Fabricated 1/4" steel	
GENERAL		
Seat	Molded Vinyl	Premium bolstered seat with built-in lumbar support
Fuel Capacity	2.8 quarts	2 gallons
Cupholder	Yes	Yes
Front Tire	11 x 4	
Drive Tire	16 x 6.50 - 8	34": 18 x 6 - 8 BigBite™ 42", 48": 18 x 8.5 - 8 BigBite™
DIMENSIONS		
Weight	34": 390 lbs 42": 400 lbs	34" deck: 455 lbs 42" deck: 467 lbs 48" deck: 490 lbs
Height	38"	40"
Length	65.5"	65.5"
Width w/Chute	34": 37.5" 42": 43.25"	34": 37.5" 42": 43.25" 48": 48.25"
Tire Width	34": 34" 42": 35.5"	34": 35" 42", 48": 41"
Trim Side	34": 0.5" 42": 2.7"	34": 0.5" 42": 2.7" 48": 4"
PRODUCTIVITY*		
Acres Per Hour	34": 1.38 42": 1.70	34": 1.65 42": 2.04 48": 2.33

* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.

** Specifications are subject to change without notice.